





BOOK TAG DISPENSER

Refining the Conversion of Your Valuable Library Assets The APTQ Book Tag Dispenser offers a specialized solution for the creation, programming, and distribution of library labels for a broad range of materials including books and magazines.

Advanced Technological Integration

The APTQ Book Tag Dispenser serves as a swift and efficient instrument, capable of writing data into book tags and adjusting the EAS and/or AFI bit as necessary. This data can be accessed via barcode scanning during the conversion

process. The dispenser functions as a standalone USB device, requiring a connection to a computer or laptop, and operates seamlessly with the YourLib® ID Converter software.

Upon completion of programming, the tag can be effortlessly removed from the release paper of the roll. Following this, a new tag will be automatically prepared for programming. The motor-driven dispenser can accommodate a wide variety of labels, with the photocell accurately detecting the beginning of each new label.

BOOK TAG DISPENSER

Specifications

Features

Conversion from barcode to RFID tag	•
Standard USB connection	•
Set/Reset EAS and/or AFI bit	•

● Included ○ Optional

Designed to work in any environment	•
Integrated RFID reader	•
Easy to install	•

Technical specs

Category	Brand new
Width (antenna)	320 mm
Height (antenna)	442 mm
Depth (antenna)	295 mm
Weight	9kg
Max. roll diameter	27,5 cm
Average speed	375 tags per hour
Compatible protocols	ISO 15693 / ISO 18000-3 mode 1
Communication interface	USB
Software	YourLib® ID Converter, optional with YourLib® Advanced Repair license
Applications	Libraries, Archives
Power	120 V (necessary power cable included)

Product reference

SKII	RFID-RTD-N

RFID specifications

Operating frequency	13.56 MHz
Technology	Advanced RFID technology
Supported tags	iCode Ilt, iCode Sli-(X)(2), 50x50mm and 50x80mm tags
Supported datamodels	3M (numeric and alphanumeric), Danish, Dutch, ISO 28560 fix, ISO 28560 object



